



## **SPECIFICATION FIRE FIGHTING SUIT**

**EN469 CE CERTIFIED FIRE SUIT  
MODEL NO : HTMA2015019510**

**Outer shell : NOMEX IIIA**

**Aramid fabric, 93% Meta aramid, 5% Para aramid, 2% Antistatic  
Twill weave, weight 240g/m<sup>2</sup>, with water repellent finish.**

**Colors: Yellow**

**Main Features :**

- **Light weight and flexible**
- **Budget cost, high value**
- **Designed and made according to the requirements to EN469**

**Moisture Barrier :**

**DENTIK, DYP14-1, made of aramid fiber spunlace substrate laminated  
with flame and heat resistant PTFE membrane, 120g/m<sup>2</sup>.**

**The functional membrane is laminated with the substrate after special  
stretching process to become microporous and to become water  
resistant, moisture permeating and breathable.**

**Thermal Barrier :**

**XF-70 Weight 240g/m<sup>2</sup>, made of meta aramid and para aramid spunlace  
material, with a comfort face cloth made of aramid and flame resistant  
cellulous fiber. Flame resistant and heat insulating.**

**Comfortable layer : XV343**

**Reflective Tape : 3M 9587 # or similar product**

**Safety Standard : EN469 CE certified**